# MATERIAL SAFETY DATA SHEET

## PETROFERM INC.

2416 Lynndale Road Fernandina Beach, Florida 32034 (904) 261-8286 www.petroferm.com

CHEMTREC 24-HOUR EMERGENCY RESPONSE **TOLL FREE NUMBER:** (800) 424-9300

**INTERNATIONAL CALLS:** COLLECT (703) 527-3887

CHEMTREC should only be contacted in the event of chemical emergencies involving a spill, leak, fire, exposure, or accident involving chemicals

### 1. PRODUCT NAME LENIUM®\* CP

### 2. **COMPOSTION AND INFORMATION ON INGREDIENTS**

	<b>CAS Number</b>	Weight %	OSHA PEL	ACGIH TLV
n-Propyl bromide	106-94-5	10 -30	25 ppm**	Not est.
Methyl Nonafluorobutyl ether	163702-07-6	30 - 40	750 ppm**	Not est.
Methyl Nonafluoroisobutyl ether	163702-08-7	30 - 40	750 ppm**	Not est.
1,2 Epoxybutane	106-88-7	< 1	Not est.	Not est.
2-Methyl-2-propanol	75-65-0	< 2	100 ppm	100 ppm
Dimethoxymethane	109-87-5	< 2	1000 ppm	1000 ppm
2-Propanol	67-63-0	3 - 8	400 ppm	400 ppm
**Source of Exposure Limit Data: Manufacturer's TWA				

<sup>&#</sup>x27;Source of Exposure Limit Data: Manufacturer's TWA

### **HAZARDS IDENTIFICATION 3.** SYMPTOMS/EFFECTS OF OVEREXPOSURE

Inhalation: May irritate the nose, throat, and lungs. Exposure to high doses may cause

> central nervous system depression (anesthetic-like effects). Doses which cause anesthetic-like effects may also cause adverse effects in liver, lung, and

kidney.

Ingestion: Low order of toxicity. May cause mild nausea and abdominal discomfort

Skin: Prolonged exposure will cause a skin irritation. Contact with eyes may cause mild irritation. **Eyes:** 

Listed Carcinogens: None

#### 4. FIRST AID MEASURES

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing

is difficult, give oxygen. Consult a physician.

**Ingestion:** Do not induce vomiting. Seek medical attention.

Skin: Remove contaminated clothing. Thoroughly wash affected area with soap

water; use skin cream if irritation is severe.

Immediately flush eyes with water for 15 minutes. Call a physician if **Eyes:** 

irritation persists.

#### 5. FIRE FIGHTING MEASURES

Extinguishing Media: Dry chemical, chemical foam, carbon dioxide. Class BC, ABC fire extinguisher.

Special Fire Fighting Procedures: Wear full protective clothing, including helmet, selfcontained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

<sup>\*</sup>Registered trademark of Petroferm Inc.

LENIUM CP 3/8/04

## 5. FIRE FIGHTING MEASURES

### **CONTINUED**

**Unusual Fire and Explosions Hazard:** Vapors can travel considerable distances to source of ignition. Exposure to extreme heat can give rise to thermal decomposition.

## 6. ACCIDENTAL RELEASE MEASURES

Absorb spill with inert material, then place in chemical waste container. Clean up residue with an appropriate organic solvent. For large spills, dike for later disposal. Observe government regulations.

## 7. HANDLING AND STORAGE

Store in original container, preferably in a cool ventilated, fire-resistant building. Avoid overheating or freezing. Avoid open flames and sparks. Since empty containers may retain product residues (vapor, liquid, or solid) all label precautions must be observed.

## 8. EXPOSURE CONTROLS – PERSONAL PROTECTION

**Respiratory:** Use NIOSH/MSHA approved respirator if ventilation is not sufficient

and if mists are generated.

**Ventilation:** If desirable to reduce odor, local exhaust can also be effective in

minimizing odor. Provide sufficient ventilation to maintain emissions

below recommended exposure limits.

**Clothing/Glove:** Chemically resistant gloves should be used with all industrial

chemicals.

**Eye Protection:** Safety glasses/goggles are recommended. Provide eye bath near

work site.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point (760 mm Hg):  $130^{\circ}$ F Vapor Density (Air -= 1): >1

(54°C)

% Volatile (By weight): 100 Evaporation Rate (BUAC = 1): < 1

**Specific Gravity (H2O = 1):** 1.43 @ 77°F **Solubility in Water**: Negligible

(25°C)

Vapor Pressure (20°C): 150 mm Hg Appearance and Odor: Clear colorless

liquid with a slight ethereal odor.

Flash Point: None (ASTM D93-85, Pensky- Flammable Limits

Martens Closed Cup) (% By Volume in Air): Not determined

## 10. STABILITY AND REACTIVITY

**Stability:** LENIUM CP is stable

**Conditions to Avoid:** Storage temperatures above 130°F.

**Incompatibility:** Strong mineral acids and strong oxidizing agents. Prolonged contact

with aluminum, magnesium, and zinc metals should be avoided.

**Hazardous Decomposition Products:** Thermal decomposition products are known to

be hazardous.

Hazardous Polymerization: Will not occur.

## 11. TOXICOLOGICAL INFORMATION

Methyl Nonafluorobutyl ether and Methyl Nonafluoroisobutyl ether

LD50/oral/rat = >5,000 mg/kg

Acute inhalation lethal concentration = > 100,000 ppm (rat, 4 hour).

Developmental toxicity: No abnormal effects observed.

LENIUM CP 3/8/04

## 11. TOXICOLOGICAL INFORMATION

**CONTINUED** 

Mutagenicity: Not a mutagen in reverse mutation or chromosomal aberration assays. Cardiac sensitization: No signs of sensitization at exposures up to 100,000 ppm.

Dermal sensitization: Not a skin sensitizer.

2-Propanol

LD50/oral/rat = 5,500 mg/kg

LD50/dermal/rabbit = 12,900 mg/kg

LC50/rat = 19,000 ppm (female); 22,500 ppm (male)

n-Propyl bromide

LD50/oral/rat = 4,260 mg/kg

 $LC50/rat = 253,000 \text{ mg/m}^3/0.5 \text{ hour}$ 

1,2 epoxybutane

LD50/oral/rat = 500 mg/kg

LD50/dermal/rabbit = 2,100 ul/kg

2-Methyl-2-propanol

LD50/oral/rat = 3,500 mg/kg

Dimethoxymethane

LC50/rat = 15,000 ppm

## 12. ECOLOGICAL INFORMATION

No information available.

## 13. DISPOSAL CONSIDERATIONS

Waste treat or incinerate used material in compliance with all applicable government regulations.

## 14. TRANSPORT INFORMATION

Non-regulated.

## 15. REGULATORY INFORMATION

The product contains 1,2 epoxybutane and 2-methyl-2-propanol which are subject to the reporting requirements of SARA Title III, Section 313. No other components of LENIUM CP appears on any of the EPA's lists of toxic or hazardous substances.

None of the components of this product is listed in California's Safe Drinking Water and Toxic Enforcement Act of 1986 – Proposition 65 as a chemical known to cause cancer, birth defects or other reproductive harm.

All the components of this product are listed on the TSCA inventory.

## 16. OTHER INFORMATION

NFPA Codes: Health: 1 Fire: 0 Reactivity: 0

We believe that the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and of these opinions and the conditions of use of the product are not within the control of Petroferm Inc., it is the user's obligation to determine the conditions of safe use of the product.