



100% Biobased Solvent & Stripper

Technical Data Sheet

AMAIZEING™ 100% Biobased Solvent & Stripper

100% blend of corn and soybean esters

DESCRIPTION

The aMAIZEing™ 100% Biobased Solvent & Stripper is based on a combination of corn and soybean oil esters designed to lift and remove mastics, adhesives, paint and more from concrete, masonry, wood, metal and a host of other surfaces. The aMAIZEing™ 100% Biobased Solvent & Stripper is 100% biobased per ASTM D 6866-04 and complies with the Federal Biobased Product Procurement Preference Program in Section 9002 of the U.S. Federal Farm Security & Rural Investment Act of 2002. The aMAIZEing™ 100% Biobased Solvent & Stripper can be used as a professional paint grade stripper; a mastic and adhesive remover; graffiti remover; lead paint remover; degreaser, parts cleaner, concrete and masonry cleaner; and much more.

The aMAIZEing™ 100% Biobased Solvent & Stripper:

- Is Readily Biodegradable
- Contains No Environmentally Hazardous Ingredients
- Contains No Ozone Depleting Chemicals (OCDs)
- Contains No Hazardous Air Pollutants
- Is 100% derived from corn and soybeans grown in the USA.

TYPICAL PHYSICAL PROPERTIES

Solids Content	ASTM D 2697	53%
Boiling Point		280°C
KB Value		240
Bio based Content	ASTM D -6866-04	100%
Health -1 / Flammability - 1 / Reactivity - 0		

STORAGE STABILITY

2 years in unopened containers.

APPLICATION INSTRUCTIONS

Apply a saturating layer by brush or sprayer. Allow product to penetrate (may require surface treatment of up to 24 hours for heavy mastics and some coatings). Before removing, test area to insure surface materials have lifted. Remove lifted materials with a rag, scraper or industrial scrubbing pad (depending on tested materials and applied surface). Reapply product if necessary to remove any leftover materials. Clean finished application area with a damp cloth and/or rinse with water or industrial pressure washer.

PRECAUTIONS

Before application of product, surface area should be tested to prevent damage to substrate. Avoid prolonged application to plastics, veneers, rubber, and vinyl as product may cause surface damage. Do not apply product to drywall or other gypsum-based materials without testing first. Avoid prolonged exposure to skin as product may cause skin sensitization in susceptible individuals. Avoid eye contact. Use product in a well ventilated area. Keep out of reach of children.

Warranties: Green Products, LLC warrants that the product will be free of manufacturer defects at the time of purchase. Under no circumstances will Green Products, LLC be liable for loss, damage, expenses or consequential damage arising out of the use or inability to use product.

