

PRODUCT PROFILE

GEO-GUARD® 2000

GEO-GUARD® 2000 is a highly alkaline non-chelating non-phosphated readily biodegradable cleaner for use in recirculating spray washers, immersion tanks, and pressure washing systems. GEO-GUARD® 2000 is especially effective at removing tough soils such as lapping compounds, grease and oil, and drawing compounds. GEO-GUARD® 2000 should be used only on ferrous metals as it will etch soft metals such as aluminum and zinc.

Key formula attributes:

- Highly alkaline base allows tough soil removal.
- Flexible temperature blend of surfactants provides low foaming high efficiency soil penetration and removal and thorough rinsing.
- Entire formulation will not interfere with normal waste treatment protocols and is readily biodegradable. Also GEO-GUARD® 2000 is not phosphated.
- Use concentrations for GEO-GUARD® 2000 range from 1% to 5% v/v for typical metal cleaning operations in a recirculating spray washer. Stronger solutions 10% to 15% v/v may be required for heavily soiled parts or cleaning in immersion tanks.

GEO-GUARD® 2000 operates along a wide spectrum of temperature ranges. The product is low foaming even at 80°F. Typical temperatures range from 90°F to 140°F. GEO-GUARD® 2000 is an authorized cleaner for USDA facilities under category Al.

FAB'S AT A GLANCE

FEATURE	ADVANTAGE	BENEFIT
Excellent Alkaline/ Surfactant Package	High Efficiency Cleaning	Production Efficiency
Non-Chelating Formula	Won't Interfere with Waste Treatment	Simplified Processing
Product is Readily Biodegradable and Non- Phosphated	Environmentally Responsible	Helps Meet Regulations