



DARAGUARD® 412

Daraguard® 412 is an organic polymer specially selected to enhance tramp oil rejection of **Daraclean®** and **Daracool®** systems. **Daraguard 412** is water soluble and can be added sumpside to reduce tramp oil contamination and facilitate skimming and fluid filtration.

APPLICATIONS / STARTING DILUTIONS:

Daraguard 412 should be premixed in one gallon of dilute coolant or cleaner before adding it to the sump.

Suggested dosage: **4 ounces / 100 gallons or**
 1 quart / 1000 gallons of sump fluid

Dosage may be increased or decreased depending on the contaminants involved.

TYPICAL PHYSICAL PROPERTIES:

Appearance:	Dark amber liquid; clear to slight haze
Specific Gravity:	1.20
Wt/U.S.Gallon:	10.0#
pH, Concentrate:	5.5

AVAILABILITY:

Daraguard 412 is available in 5 gallon pails, 55 gallon drums and returnable totes.

Daraguard®, Daraclean® and Daracool® are registered trade names of W.R.Grace & Co.-Conn.

W.R. Grace & Co.-Conn., Metalworking Fluids Group

5225 Phillip Lee Drive, S.W. Atlanta, Georgia 30336 (404) 691-8646
6000 West 51st Street, Chicago, Illinois 60638 (708) 458-0340
55 Hayden Avenue, Lexington, Massachusetts 02173 (617) 861-6600

5205 Harvester Road, #4, Burlington, Ontario, Canada L7L 6B5 (905) 681 0285
255 Lafleur Avenue, LaSalle, Quebec, Canada H8R 3H4 (514) 366-3070
2140 Davis Street, San Leandro, California 94577 (510) 568-3427

We hope that the information given here will be helpful. It is based on our best knowledge, and we believe it to be true and accurate. Please read all statements, recommendations or suggestions herein in conjunction with our conditions of sale which apply to all goods supplied by us. We assume no responsibility for the use of these statements, recommendations or suggestions, nor do we intend them as a recommendation for any use which would infringe any patent or copyright.