

# B. C .S. Company

763 Thompson Rd., Thompson, CT 06277  
(860) 923-9575 • Fax (860) 923-2093

TECHNICAL SERVICE DATA SHEET  
251 SR  
Metal safe liquid spray wash  
Cleaner

## DESCRIPTION:

B.C.S. 251 SR is a non-caustic, liquid spray wash cleaner with a blend of alkaline builders, water conditioners, low foaming surfactants and short term corrosion inhibitors. 251 SR is suitable for ferrous and non-ferrous metals and can be used at temperatures ranging from 80 degrees F to 160 degrees F.

## ADVANTAGES:

Multi-metal safe	Low foaming
Can be used in hard water areas	Easy handling liquid
Short term in-process rust protection	Contains no phosphates

## TYPICAL APPLICATION:

The unique formulation of this product allows its use in more than one application.

Primary use - spray wash cleaner

Aluminum safe - hot tank cleaner

## USE INSTRUCTIONS:

Spray wash -  $\frac{1}{2}$  to 5% by volume, depending on soils. Use at temperatures ranging from 80 degrees F to 160 degrees F. If no history of cleaning is available start cleaning process at high percentage of cleaner and high temperature. Reduce each part until the best results are seen at the most economical concentration and temperature.

Hot tank - 3 to 8% by volume, depending on soils. Use at temperatures ranging from 140 degrees F to 160 degrees F. Agitation of tank will improve cleaning results and cleaning time.

For additional information such as physical characteristics, safety precautions, disposal, etc., see corresponding MSDS.