

MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: DS - 104 WIPE SOLVENT

GENERAL USE: Cleaning solvent

PRODUCT DESCRIPTION: Colorless combustible liquid

U.S.A. Patent No. 5,188,754



MANUFACTURER'S NAME

Dysol Inc. (formerly Dynamold Solvents, Inc.)

DATE PREPARED: October 6, 2006

SUPERSEDES: September 1, 2006

Page 1 of 4

ADDRESS (NUMBER, STREET, P.O. BOX)

2901 Shamrock Avenue

TELEPHONE NUMBER FOR INFORMATION

(817) 335-1826

MATERIAL SAFETY DATA SHEET

COUNTRY

EMERGENCY TELEPHONE NUMBER

Fort Worth, TX 76107

USA

CHEM • TEL (800) 255-3924 Outside USA (813) 248-0585

DISTRIBUTOR'S NAME

ADDRESS (NUMBER, STREET, P.O. BOX)

TELEPHONE NUMBER FOR INFORMATION

(CITY, STATE AND ZIP CODE)

COUNTRY

EMERGENCY TELEPHONE NUMBER

SECTION 2 - HAZARDOUS INGREDIENTS

HAZARDOUS COMPONENTS

CAS #

%

(by weight)

OSHA PEL

ACGIH TWA

SARA

RQ

PPM

MG/M3

PPM

MG/M3

TITLE III

LBS

Propylene glycol monomethyl ether acetate

108-65-6

65 - 70

not established

Petroleum distillate, aliphatic

64742-48-9

25 - 32

100

500

n - Butyl acetate (a)

123-86-4

3 - 5

150

710

150

5000

(a) See Section 15

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Colorless liquid, potentially hazardous vapors. Flammable as defined by DOT and TDG for Air / Ocean transport. Classified by DOT as Combustible for ground transport in containers less than 120 gallons. Classified as Combustible by OSHA. Can cause serious or fatal complications if swallowed. Can cause eye and skin irritation upon contact. Inhalation of vapors can cause anesthetic effect leading to death in poorly ventilated areas.

POTENTIAL HEALTH EFFECTS

INHALATION: High concentrations are irritating to the respiratory tract; may cause headache, dizziness, nausea, vomiting and malaise.

SKIN: Brief contact may cause slight irritation; prolonged contact may cause moderate irritation or dermatitis.

EYES: High vapor concentration or contact may cause irritation and discomfort.

INGESTION: May result in vomiting; aspiration of vomitus into the lungs must be avoided; DO NOT induce vomiting. Minute amounts aspirated into the lungs can produce severe lung injury, chemical pneumonitis, pulmonary edema or death.

CARCINOGENICITY

NTP?

No

IARC MONOGRAPHS?

No

OSHA REGULATED?

No

MATERIAL SAFETY DATA SHEET			
PRODUCT NAME: DS - 104 WIPE SOLVENT October 6, 2006			Page 2 of 4
SECTION 4 - FIRST AID MEASURES			
INHALATION: Remove affected person to fresh air; provide oxygen if breathing is difficult; if affected person is not breathing, administer CPR and seek emergency medical attention.			
SKIN: Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.			
EYES: Check for and remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.			
INGESTION: DO NOT induce vomiting; if vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs; seek immediate medical attention. Vomiting may be induced only under the supervision of a physician.			
SECTION 5 - FIRE FIGHTING MEASURES			
FLASH POINT (METHOD USED) 105° F (40.6° C) TCC		FLAMMABLE LIMITS LEL: 2.0% AUTOIGNITION TEMPERATURE: 520° F (271° C)	UEL: 10.0% NFPA CLASS: II
GENERAL HAZARDS: Product is combustible. Products of combustion include compounds of carbon, hydrogen and oxygen, including carbon monoxide.			
EXTINGUISHING MEDIA Carbon dioxide, water, water fog, dry chemical, chemical foam.			
FIRE FIGHTING PROCEDURES Self - contained respiratory equipment; cool containers to prevent pressure buildup and possible explosion when exposed to extreme heat.			
UNUSUAL FIRE AND EXPLOSION HAZARDS Closed containers can explode due to buildup of pressure when exposed to extreme heat.			
HAZARDOUS COMBUSTION PRODUCTS Smoke, fumes or vapors, oxides of carbon.			
SECTION 6 - ACCIDENTAL RELEASE MEASURES			
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: COMBUSTIBLE. Evacuate and ventilate area; confine and absorb into absorbent; place material into approved containers for disposal; for spills in excess of allowable limits (RQ) notify the National Response Center (800) 424 - 8802; refer to CERCLA 40 CFR 302 for detailed instructions concerning reporting requirements. Do not discharge into lakes, ponds, streams or public waters.			
SECTION 7 - HANDLING AND STORAGE			
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: This material is combustible. It should be stored in tightly closed containers in a cool, well ventilated area. Vapor may form explosive mixtures in air. All sources of ignition should be controlled. This material may be classified as COMBUSTIBLE by DOT unless transported by vessel or aircraft. Refer to 49 CFR 173.120. Keep this and other chemicals out of reach of children. Avoid inhaling concentrated fumes or vapors.			
SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION			
ENGINEERING CONTROLS			
The use of local exhaust ventilation is recommended to control emissions near the source. Provide mechanical ventilation of confined spaces. Use explosion-proof ventilation equipment.			
PERSONAL PROTECTION:			
RESPIRATORY PROTECTION: None required while threshold limits are kept below maximum allowable concentrations; if TWA exceeds limits, NIOSH approved respirator must be worn. Refer to 29 CFR 1910.134 or European Standard EN 149 for complete regulations.			
PROTECTIVE GLOVES: Neoprene, butyl or nitrile rubber gloves with cuffs.			
EYE PROTECTION: Chemical splash goggles. Refer to 29 CFR 1910.133 or European Standard EN166.			
OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Safety eyewash station nearby.			
WORK / HYGIENIC PRACTICES: Practice safe workplace habits. Minimize body contact with this, as well as all chemicals in general.			

MATERIAL SAFETY DATA SHEET			
PRODUCT NAME: DS - 104 WIPE SOLVENT October 6, 2006			Page 3 of 4
SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES			
VAPOR PRESSURE 4 mm Hg @ 20° C		VAPOR DENSITY (AIR = 1) > 1	
SPECIFIC GRAVITY (WATER = 1) 0.890		EVAPORATION RATE (Water = 1) < 1	
SOLUBILITY IN WATER Appreciable, 20%		FREEZING POINT Not determined	
pH Not applicable		APPEARANCE AND ODOR Colorless liquid, strong fruity odor	
BOILING POINT 250° F (121° C)		PHYSICAL STATE Liquid	
VISCOSITY Approximately that of water		VOLATILE ORGANIC COMPOUNDS (Total VOC's) 7.4 lbs / gal (895 gms / liter)	
SECTION 10 - STABILITY AND REACTIVITY			
STABILITY UNSTABLE: STABLE: XXX		CONDITIONS TO AVOID: Extreme temperatures, open flames.	
INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, strong acids.			
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes or vapors, and smoke may be produced.			
HAZARDOUS POLYMERIZATION MAY OCCUR: WILL NOT OCCUR: XXX		CONDITIONS TO AVOID: None	
SECTION 11 - TOXICOLOGICAL INFORMATION			
Hazardous Ingredients	CAS #	LD50 of Ingredient (Specify Species and Route)	LC50 of Ingredient (Specify Species)
Propylene glycol monomethyl ether acetate	108-65-6	8532 mg / kg Oral - rat	Not established
Petroleum distillate, aliphatic	64742-48-9	Not determined	Not determined
n - Butyl acetate (a)	123-86-4	14,000 mg / kg Oral - rat	> 6335 ppm / 4H Inhalation - rat
SECTION 12 - ECOLOGICAL INFORMATION			
No data are available on the adverse effects of this material on the environment. Neither COD nor BOD data are available. Based on the chemical composition of this product it is assumed that the mixture can be treated in an acclimatized biological waste treatment plant system in limited quantities. However, such treatment should be evaluated and approved for each specific biological system. None of the ingredients in this mixture are classified as a Marine Pollutant.			
SECTION 13 - DISPOSAL CONSIDERATIONS			
WASTE DISPOSAL METHOD: Dispose of in accordance with Local, State, and Federal Regulations. This product may produce hazardous vapors in a closed disposal container creating a dangerous environment. Refer to "40 CFR Protection of Environment Parts 260 - 299" for complete waste disposal regulations. Consult your local, state, or Federal Environmental Protection Agency before disposing of any chemicals. Do not flush to sanitary sewer or waterway.			
SECTION 14 - TRANSPORT INFORMATION			
PROPER SHIPPING NAME: Flammable liquid, n.o.s. (propylene glycol methyl ether acetate / n-butyl acetate). Note: Not regulated for ground transport in containers < 120 gallons. Flammable liquids, n.o.s. for air / ocean transport.			
DOT HAZARD CLASS / Pack Group: 3 / III REFERENCE: 49 CFR 173.150, .203, .242 UN / NA IDENTIFICATION NUMBER: UN 1993 LABEL: FLAMMABLE LIQUID			
HAZARD SYMBOLS: F Hazard Identification Number (HIN): 30			
Note: Transportation information provided is for reference only. Client is urged to consult CFR 49 parts 100 - 177, IMDG, IATA, EC, United Nations TDG, and WHMIS (Canada) TDG information manuals for detailed regulations and exceptions covering specific container sizes, packaging materials and methods of shipping.			

MATERIAL SAFETY DATA SHEETPRODUCT NAME: DS - 104 WIPE SOLVENT
October 6, 2006

Page 4 of 4

SECTION 15 - REGULATORY INFORMATION**TSCA (Toxic Substance Control Act)**

All components of this product are listed on the U.S. Toxic Substances Control Act Chemical Inventory (TSCA Inventory) or are exempted from listing because a Low Volume Exemption has been granted in accordance with 40 CFR 723.50.

SARA TITLE III (Superfund Amendments and Reauthorization Act)

311/312 Hazard Categories

Fire hazard, Immediate health

313 Reportable Ingredients:

None

CERCLA (Comprehensive Response Compensation and Liability Act)

(a) The Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) has notification requirements for releases or spills to the environment of the Reportable Quantity (RQ for this mixture > 24,000 lbs) or greater amounts, according to 40 CFR 302.

California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986

There are no chemicals present known to the state of California to cause cancer or reproductive toxicity.

CPR (Canadian Controlled Products Regulations)

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations. WHMIS Classification: B3, D2B

IDL (Canadian Ingredient Disclosure List)

Components of this product identified by CAS number and listed on the Canadian Ingredient Disclosure List are shown in Section 2.

DSL / NDSL (Canadian Domestic Substances List / Non-Domestic Substances List)

Components of this product identified by CAS number are listed on the DSL or NDSL, or are otherwise in compliance with the New Substances Notification (NSN) regulations. Only ingredients classified as "hazardous" are listed in Section 2 unless otherwise indicated.

SECTION 16 - OTHER INFORMATION

Specific toxicity tests have not been conducted on this product. Our hazard evaluation is based on Information from similar products, the ingredients, technical literature, and/or professional experience.

HMIS HAZARD RATINGS

HEALTH

1

* = Chronic Health Hazard

2 = MODERATE

FLAMMABILITY

2

0 = INSIGNIFICANT

3 = HIGH

PHYSICAL HAZARD

0

1 = SLIGHT

4 = EXTREME

PERSONAL PROTECTIVE EQUIPMENT

B

Safety Glasses, Gloves

REVISION SUMMARY:

This MSDS has been revised in the following sections:

Format update

MSDS Prepared by: Comprehensive Data Base, Inc.
P.O. Box 5604
Lakeland, FL 33807 USA
(863) 644 - 3298 www.compdatabase.com

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.