MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: DS - 801 PAINT SPRAY GUN CLEANER

GENERAL USE: Paint Spray Gun Cleaner / Cleaning solvent PRODUCT DESCRIPTION: Colorless flammable liquid



MANUFACTURER'S NAME		DATE PREPARED: January 24, 2007 Page 1 of 4			
Dysol Inc. (formerly Dynamold Solvents, Inc.)		SUPERSEDES: November 2, 2006			
ADDRESS (NUMBER, STREET, P.O. BOX)		TELEPHONE NUMBER FOR INFORMATION			
2901 Shamrock Avenue		(817) 335-1826			
MATERIAL SAFETY DATA SHEET	COUNTRY	EMERGENCY TELEPHONE NUMBER			
Fort Worth, TX 76107	USA	CHEM • TEL (800) 255-3924 Outside USA (813) 248-0585			
DISTRIBUTOR'S NAME					
Same					
ADDRESS (NUMBER, STREET, P.O. BOX)		TELEPHONE NUMBER FOR INFORMATION			
(CITY, STATE AND ZIP CODE)	COUNTRY	EMERGENCY TELEPHONE NUMBER			
SECTION 2 - HAZARDOUS INGREDIENTS					

HAZARDOUS COMPONENTS (by weight) PPM MG/M3 PPM MG/M3 107-98-2 65 - 85 360 100 Propylene glycol monomethyl ether 100 67-64-1 25 - 35 1000 2400 500 5000 Acetone (a,b)

(a) See Section 15

(b) Indicates that the Resource Conservation and Recovery Act (RCRA) has determined the waste for this chemical is listed as hazardous and must be handled according to regulations in 40 CFR 260-281.

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Colorless highly flammable liquid, hazardous vapors. Can cause serious or fatal complications if swallowed. Can cause eye and skin irritation upon contact. Inhalation of vapors can cause anesthetic effect leading to death in poorly ventilated areas.

POTENTIAL HEALTH EFFECTS

INHALATION: High concentrations are irritating to the respiratory tract; may cause headache, dizziness, nausea, vomiting and malaise.

SKIN: Brief contact may cause slight irritation; prolonged contact may cause moderate reddening, swelling and possible necrosis.

EYES: Contact causes severe irritation and pain associated with redness and swelling of the conjunctiva.

INGESTION: Moderately toxic; may cause headache, dizziness, diarrhea and general weakness; large doses may result in red blood cell hemolysis.

CARCINOGENICITY NTP? No IARC MONOGRAPHS? NO OSHA REGULATED? NO

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: DS - 801 PAINT SPRAY GUN CLEANER

January 24, 2007

SECTION 4 - FIRST AID MEASURES

INHALATION: Remove affected person to fresh air; provide oxygen if breathing is difficult; if affected person is not breathing, administer CPR and seek emergency medical attention.

SKIN: Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.

EYES: Check for and remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.

INGESTION: Give two glasses of water for dilution; Induce vomiting by sticking fingers down throat; never give anything by mouth to an unconscious person; seek medical attention.

SECTION 5 - FIRE FIGHTING MEASURES

FLAMMABLE LIMITS UEL: 12.8% FLASH POINT (METHOD USED) LEL: 2.6% **AUTOIGNITION TEMPERATURE:** 869° F (465° C) NFPA CLASS: -2° F (-18.9° C) TCC

GENERAL HAZARDS: Product is flammable. Products of combustion include compounds of carbon, hydrogen and oxygen, including carbon monoxide.

EXTINGUISHING MEDIA

Carbon dioxide, water, water fog, dry chemical, chemical foam.

FIRE FIGHTING PROCEDURES

Self - contained respiratory equipment; cool containers to prevent pressure buildup and possible explosion when exposed to extreme heat. Caution - material is flammable!

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers can explode due to buildup of pressure when exposed to extreme heat. Vapors may cause a flash fire or ignite explosively. Vapors may travel a considerable distance to a source of ignition and flash back.

HAZARDOUS COMBUSTION PRODUCTS

Smoke, fumes or vapors, oxides of carbon.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: CAUTION - FLAMMABLE - Evacuate and ventilate area; confine and absorb into absorbent; place material into approved containers for disposal; for spills in excess of allowable limits notify the National Response Center (800) 424 - 8802; refer to CERCLA 40 CFR 302 for detailed instructions concerning reporting requirements. Do not discharge into lakes, ponds, streams or public waters.

SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep container closed when not in use; protect containers from abuse; protect from extreme temperatures. CAUTION - FLAMMABLE - keep away from all sources of ignition. "Empty" containers may contain residue which may form explosive vapors. Do not weld or cut near empty container that has not been professionally reconditioned. Use nonsparking tools when opening and closing containers. Maintain well ventilated work areas to minimize exposure when handling this material.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS

The use of local exhaust ventilation is recommended to control emissions near the source. Provide mechanical ventilation of confined spaces. Use explosion-proof ventilation equipment.

PERSONAL PROTECTION:

RESPIRATORY PROTECTION: None required while threshold limits are kept below maximum allowable concentrations: if TWA exceeds limits, NIOSH approved respirator must be worn. Refer to 29 CFR 1910.134 or European Standard EN 149 for complete regulations.

PROTECTIVE GLOVES: Neoprene, butyl or nitrile rubber gloves with cuffs.

EYE PROTECTION: Chemical splash goggles. Refer to 29 CFR 1910.133 or European Standard EN166.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Safety eyewash station nearby.

WORK / HYGIENIC PRACTICES: Practice safe workplace habits. Minimize body contact with this, as well as all chemicals in general.

Page 2 of 4

ΙB

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: DS - 801 PAINT SPRAY GUN CLEANER
January 24, 2007

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

VAPOR PRESSURE

VAPOR DENSITY (AIR = 1)

185 mm Hg @ 20° C SPECIFIC GRAVITY (WATER = 1) EVAPORATION RATE (Water = 1) 0.66 SOLUBILITY IN WATER FREEZING POINT Complete Not determined APPEARANCE AND ODOR pН Colorless liquid, characteristic ketone odor Not applicable PHYSICAL STATE **BOILING POINT** 132° F (56° C) Liquid VOLATILE ORGANIC COMPOUNDS (Total VOC's) VISCOSITY

SECTION 10 - STABILITY AND REACTIVITY

5.35 lbs / gal (641 gms / liter)

STABILITY UNSTABLE: CONDITIONS TO AVOID: Extreme temperatures, open flames, sparks.

STABLE: X

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, strong acids.

50 cps @ 25° C

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes or vapors, and smoke may be produced.

HAZARDOUS POLYMERIZATION MAY OCCUR: CONDITIONS TO AVOID: None

WILL NOT OCCUR: X

SECTION 11 - TOXICOLOGICAL INFORMATION

CECTION II TOMOCECUIONE IN CITION					
Hazardous Ingredients	CAS#	LD50 of Ingredient (Specify Species and Route)	LC50 of Ingredient (Specify Species)		
Propylene glycol monomethyl ether	107-98-2	5660 mg / kg Oral - rat	10,000 ppm / 5H Inhalation - rat		
Acetone (a,b)	67-64-1	9750 mg / kg Oral - rat	16,000 ppm / 4H Inhalation - rat		

SECTION 12 - ECOLOGICAL INFORMATION

No data are available on the adverse effects of this material on the environment. Neither COD nor BOD data are available. Based on the chemical composition of this product it is assumed that the mixture can be treated in an acclimatized biological waste treatment plant system in limited quantities. However, such treatment should be evaluated and approved for each specific biological system. None of the ingredients in this mixture are classified as a Marine Pollutant.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of in accordance with Local, State, and Federal Regulations. This product may produce hazardous vapors in a closed disposal container creating a dangerous environment. Refer to "40 CFR Protection of Environment Parts 260 - 299" for complete waste disposal regulations. Consult your local, state, or Federal Environmental Protection Agency before disposing of any chemicals. Do not flush to sanitary sewer or waterway.

SECTION 14 - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Paint related material

DOT HAZARD CLASS / Pack Group: 3 / II

REFERENCE: 49 CFR 173.150, .173, .242

UN / NA IDENTIFICATION NUMBER: UN 1263 HAZARD SYMBOLS: F

LABEL: FLAMMABLE LIQUID Hazard Identification Number (HIN): 33

Note: Transportation information provided is for reference only. Client is urged to consult CFR 49 parts 100 - 177, IMDG, IATA, EC, United Nations TDG, and WHMIS (Canada) TDG information manuals for detailed regulations and exceptions covering specific container sizes, packaging materials and methods of shipping.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: DS - 801 PAINT SPRAY GUN CLEANER

January 24, 2007

Page 4 of 4

SECTION 15 - REGULATORY INFORMATION

TSCA (Toxic Substance Control Act)

All components of this product are listed on the U.S. Toxic Substances Control Act Chemical Inventory (TSCA Inventory) or are exempted from listing because a Low Volume Exemption has been granted in accordance with 40 CFR 723.50.

SARA TITLE III (Superfund Amendments and Reauthorization Act)

311/312 Hazard Categories

Fire hazard, Immediate health

313 Reportable Ingredients:

None

CERCLA (Comprehensive Response Compensation and Liability Act)

(a) The Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) has notification requirements for releases or spills to the environment of the Reportable Quantity (RQ for this mixture > 24,000 lbs) or greater amounts, according to 40 CFR 302.

California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986

There are no chemicals present known to the state of California to cause cancer or reproductive toxicity.

CPR (Canadian Controlled Products Regulations)

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations. WHMIS Classification: B2, D2B

IDL (Canadian Ingredient Disclosure List)

Components of this product identified by CAS number and listed on the Canadian Ingredient Disclosure List are shown in Section 2.

DSL / NDSL (Canadian Domestic Substances List / Non-Domestic Substances List)

Components of this product identified by CAS number are listed on the DSL or NDSL, or are otherwise in compliance with the New Substances Notification (NSN) regulations. Only ingredients classified as "hazardous" are listed in Section 2 unless otherwise indicated.

SECTION 16 - OTHER INFORMATION

Specific toxicity tests have not been conducted on this product. Our hazard evaluation is based on Information from similar products, the ingredients, technical literature, and/or professional experience.

HMIS HAZARD RATINGS HEALTH 1 * = Chronic Health Hazard 2 = MODERATE

FLAMMABILITY 3 0 = INSIGNIFICANT 3 = HIGHPHYSICAL HAZARD 0 1 = SLIGHT 4 = EXTREME

PERSONAL PROTECTIVE EQUIPMENT B Safety Glasses, Gloves

REVISION SUMMARY:

This MSDS has been revised in the following sections: Section 9: Correction of Volatile Organic Compounds

MSDS Prepared by: Comprehensive Data Base, Inc.

P.O. Box 395

Intercession City, FL 33848 USA

(863) 644 - 3298 www.compdatabase.com or www.msds.cc

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.