MATERIAL SAFETY DATA SHEET

Daraclean 283

1. **IDENTIFICATION**

UARACLEAN®

Company:	MAGNAFLUX
Address:	3624 West Lake Avenue, Glenview, Illinois 60026
Telephone No.:	(847) 657-5300 (Off-Hour Emergency Number - CHEMTREC - 1-800-424-9300).
Product Use:	Aqueous alkaline cleaner
Packages:	5 gallon pail, 55 gallon drum
NFPA Rating:	Health 2, Flammability 0, Reactivity 0
PIN:	None
Revision Date:	September 5, 2007

2. INGREDIENTS

	CAS Number	<u>% by Weight</u>	OSHA PEL	ACGIH TLV
Hazardous Ingredients				
Sodium Hydroxide	1310-73-2	1 – 5	2 mg/m ³	Not available

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW Bland, nonflammable, thin liquid which may irritate the skin and eyes.

	Signs & Symptoms of Acute Exposure
Inhalation:	Irritation may occur if material becomes airborne.
Eyes:	Irritation upon direct contact.
Skin:	Irritation upon direct contact.
Ingestion:	None known.

4. FIRST AID

Skin Contact:	Wash off with soap and water. Use soothing lotion.
Eyes:	Rinse carefully under upper and lower eyelids using plenty of water.
Inhalation:	Remove to fresh air.
Ingestion:	If conscious, dilute by giving 2 glasses of water. Call physician or local poison control center immediately.
NOTE: In all severe cases, contact physician immediately. Local telephone operators can furnish number of regional poison control center.	

5. FIRE HAZARD

Conditions of flammability:	None
Flash point:	None to boiling
Flammable limits in air:	None
Extinguishing media:	Carbon Dioxide, dry chemical, foam. Avoid water if possible. Special fire fighting procedures: None
Hazardous combustion products:	Combustion will result in the release of the usual decomposition products including oxides of carbon and
	nitrogen.
Unusual fire hazards:	None

6. ACCIDENTAL RELEASE MEASURES

For Small Spills:Wipe up, or absorb with sand or other absorbent material. Collect waste in sealed containers.For Large Spills:Dike area to prevent spreading. Shovel or pump to drum or salvage tank. Absorb residual material with sand, or other
absorbent material. Wash area with soapy water and rinse. Area will be slippery until cleaned.

Dispose of all product wastes and water rinses in accordance with current local, state, and Federal regulations.

7. HANDLING AND STORAGE

-Does not normally become airborne; in operations where it does, if general ventilation or local exhaust is inadequate, persons exposed to mists should wear approved breathing devices.

-Wear neoprene gloves if direct contact likely; wear eye protection.

-Store product at 40-100°F in a well-ventilated area.

-Do not mix with nitrites or nitrite containing compounds (49 FR 24658, 6/14/84).



A Division of Illinois Tool Works Inc. 3624 WEST LAKE AVENUE ■ GLENVIEW, ILLINOIS 60026 TEL 847.657.5300 ■ FAX 847.657.5388 www.magnaflux.com Page 1 of 2 Daraclean 283

DARACLEAN®

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection:	None
Ventilation:	Mechanical (general) sufficient
Protective gloves:	Recommended (rubber)
Eye protection:	Recommended
Work/Hygienic practices:	Avoid breathing spray mist

9. PHYSICAL PROPERTIES

Initial boiling point (bulk): Percent volatile: Density/sp. gravity: Water solubility: pH of concentrate:

10. STABILITY AND REACTIVITY

Stability:StableIncompatibility:NoneHazardous decomposition products:NoneReactivity:None

11. <u>TOXICOLOGICAL INFORMATION</u> Carcinogenicity:

 Carcinogenicity:
 Contains no known or suspected carcinogens listed with OSHA, IARC, NTP, or ACGIH.

 Threshold limit value:
 Not established.

 WHMIS information (Canada):
 According to available information, the ingredients have not been found to show reproductive toxicity, teratogenicity, mutagenicity, skin sensitization, or synergistic toxic effects with other materials.

requirements may be more restrictive than federal laws and regulations.

12. ECOLOGICAL INFORMATION

No data is available. It dissolves into water and is biodegradable. Its low vapor pressure may exempt it from VOC restrictions.

13. DISPOSAL

Dispose according to Federal, State and Local laws and 40 CFR. RCRA: This product, if deemed unusable and classified as "waste" is a RCRA hazardous waste carrying waste code

212°F approx

1.0 appro.

100%

13.0

Not Established

Note:

D002 (Corrosive). Chemical additions to, processing of, or otherwise altering this material may make this waste management information inaccurate, incomplete, or otherwise inappropriate. Furthermore, state and local waste disposal

Vapor pressure:

Evaporation rate:

Vapor density:

Appearance:

23 mmHg @ 20°C

None established

1.0 (water = 1.0)

Clear/slightly hazy yellow liquid

14. TRANSPORTATION

U.S. DOT: 49 CFR 172.101 Hazardous Materials Table

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification No.:	None
Packing Group:	None

15. **REGULATORY INFORMATION**

 TSCA:
 All ingredients are listed in TSCA inventory.

 CERCLA:
 Not reportable.

 SARA TITLE III, Section 313:
 Contains no toxic chemicals above 1%, or any carcinogenic chemicals above 0.1%.

 California Proposition 65:
 Warning: This material may contain trace amounts of chemicals known to the state of California to cause cancer and/or birth defects and/or reproductive harm.

 WHMIS Class (Canada):
 Not a controlled product.

Note: This MSDS has been prepared to meet WHMIS (Canada) requirements with the exception of using 16 headings.

16. OTHER INFORMATION

Revision Statement:	Section 13
Supersedes:	October 26, 2004
Prepared by:	Tamie Simmons, Research Manager



A Division of Illinois Tool Works Inc. 3624 WEST LAKE AVENUE ■ GLENVIEW, ILLINOIS 60026 TEL 847.657.5300 ■ FAX 847.657.5388 www.magnaflux.com Page 2 of 2 Daraclean 283