



DARACLEAN

AQUEOUS CLEANERS

DARACLEAN® 200

AQUEOUS CLEANING SOLUTION

- SCAQMD Certified
- Low Foam Levels
- Citrus Fragrance
- Zero VOCs
- RoHS Compliant
- Multi-Metal Safe
- Corrosion Inhibitors
- No Phosphates
- No Chlorine, Sulfur

• **Safe and Effective**

DARACLEAN® 200 is a low-foaming, all-purpose alkaline cleaning solution. Formulated with a blend of surfactants, emulsifiers, and corrosion inhibitors, DARACLEAN® 200 is an excellent cleaner for use on a broad spectrum of soils. Designed to be used with immersion, spray, and ultrasonic applications, it is safe to use with most metals and is non-aggressive towards brass, copper, and titanium alloys.

• **Industrial Strength**

DARACLEAN® 200 has proven ability at removing machine oils, lube oils, cutting fluids, buffing compounds, and even tough, carbonized soils. Using aggressive alkaline chemistry, heavy petroleum-based oils and carbonized soils are broken down and pulled free from part surfaces. Easy to use and maintain, DARACLEAN® 200 is also Clean Air Certified to SCAQMD requirements.

• **Soil Rejecting**

DARACLEAN® 200 has excellent soil-rejecting qualities. After soils are lifted from part surfaces, they are suspended in the cleaner for a short time. Over time, solids will settle out, and oil and grease droplets will coalesce and float on the surface of the solution. Removal of soils can easily be accomplished using filters or skimmers as necessary. This action extends the useful life of DARACLEAN® 200 much further than emulsion-type cleaning solutions.

Typical Applications

Cleaning Method	Concentration	Temperature	Typical Duration
Immersion	3–25%	80–180°F (27–82°C)	2–30 minutes
Ultrasonic	3–25%	80–180°F (27–82°C)	2–30 minutes
Spray	1–12% 2–5% Recommended	130–180°F (54–82°C)	0.25–3 minutes
Steam	1–12%	150–200°F (66–93°C)	1–5 minutes

**Operating parameters should be optimized for each individual application.*

MAGNAFLUX®

A Division of Illinois Tool Works Inc.

3624 WEST LAKE AVENUE ■ GLENVIEW, ILLINOIS 60026

TEL 847.657.5300 ■ FAX 847.657.5388

www.magnaflux.com


Specifications are subject to change without prior notice or obligation.
Rev. 06K01 • © 2006 Magnaflux

DARACLEAN® 200

pH Level	13–14 Caustic		Higher pH cleaners are more aggressive and will clean tougher soils but high pH levels can corrode or etch soft metal surfaces.
	11–13 High Alkaline		
	9–11 Alkaline		
	7–9 Neutral		
Foam Level	High		High foam levels will penetrate cracks and holes better, but foam cannot be tolerated in spray applications.
	Moderate		
	Low		
Silicates	Yes	No	Silicates prevent corrosion of metal surfaces, but can form mineral films at high temperatures.
Phosphates	Yes	No	Phosphates provide excellent cleaning action, but are subject to environmental regulations.
Hard Water Tolerance	High		Hard water can suppress cleaning actions—some cleaners are formulated to counteract hard water effects.
	Moderate		
	Low		
Aerospace Compliant	Yes	No	See list for specification compliance
SCAQMD Certified	Yes	No	VOC (10%) 0.0 g/L

Legend: Correct Application

Excellent	Good	Fair	Poor	Not Recommended	Aluminum	Anodized Aluminum	Brass & Bronze	Carbon Steel & Cast Iron	Copper	Magnesium	Nickel & Superalloys	Plating (Cd, Cr, Ir, Pt)	Stainless Steel	Titanium	Zinc
★★★★	★★★	★★	★												
Water-Soluble Oils	★★				★★		★★	★★★★	★★		★★★★	★★	★★★★	★★	
Machining Fluids	★★				★★		★★	★★★★	★★		★★★★	★★	★★★★	★★	
Synthetic Coolants	★★				★★		★★	★★★★	★★		★★★★	★★	★★★★	★★	
Medium Weight Oils	★★				★★		★★	★★★★	★★		★★★★	★★	★★★★	★★	
Lube Oils	★★				★★		★★	★★★★	★★		★★★★	★★	★★★★	★★	
Buffing Compounds	★★				★★		★★	★★★★	★★		★★★★	★★	★★★★	★★	
Motor Oils	★★				★★		★★	★★★★	★★		★★★★	★★	★★★★	★★	
Heavy Petroleum Oils	★★				★★		★★	★★★★	★★		★★★★	★★	★★★★	★★	
Carbonized Soils	★★				★★		★★	★★	★★		★★	★★	★★	★★	
Railroad & Axle Grease	★				★		★	★★	★		★★	★	★★	★	
Glues	★				★		★	★★	★		★★	★	★★	★	
Spray Adhesives															



NFPA Rating (Concentrate)

DARACLEAN® 200

5 US Gallons (18.9 liters)

P/N 01-6020-40

DARACLEAN® 200

55 US Gallons (208 liters)

P/N 01-6020-45

MAGNAFLUX®

A Division of Illinois Tool Works Inc.

3624 WEST LAKE AVENUE ■ GLENVIEW, ILLINOIS 60026

TEL 847.657.5300 ■ FAX 847.657.5388

www.magnaflux.com

Specifications are subject to change without prior notice or obligation.
Rev. 06K01 • © 2006 Magnaflux