MANUFACTURER

Finger Lakes Chemicals 420 St. Paul Street Rochester, NY 14605 1-800-876-0222 EMERGENCY (585) 275-3232

MATERIAL SAFETY DATA SHEET

Hazard: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme. Protection: A-Goggles, B-Goggles & gloves, C-Goggles, gloves, & protective wear. Other: NA-Not Applicable, ND-Not Determined, NE-Not Established.

HAZARD RATING Health Fire

Reactivity 0 Protection В

SECTION I DESCRIPTION

TRADE NAME: Finger Lakes Formula T[™]

PRODUCT TYPE: Brake Parts Cleaner

SECTION II HAZARDOUS INGREDIENTS					
NGREDIENT	CAS#	PEL	TLV	STEL	%
Alpha Terpineol	98-55-5	NE	NE	NE	<15 %
Ether Carboxylate	67990-14-4	NE	NE	NE	< 5 %
Diethylene Glycol Monobutyl Ether	112-34-5	NE	NE	NE	<20 %
Metapenta J	6834-92-0	NE	NE	NE	< 3 %
		SECTION III	PHYSICAL DATA		
BOILING POINT:	428°F	SPECIFIC GRAVITY (H ₂ O=1):		1.01	pH: 10-11
/APOR PRESSURE:	<0.2 MMHG	PERCENT V	PERCENT VOLATILE BY VOL %:		·
/APOR DENSITY (air=1):	5.3	EVAPORATI	EVAPORATION RATE (Butyl Acetate=1):		
SOLUBILITY IN WATER:	<1%	APPEARANCE & ODOR:		Amber/Pine scent	

FLASH POINT (method used): 212°F (TCC) EXTINGUISHING MEDIA: Water fog, foam, CO₂, or dry chemical.

LOWER EXPLOSIVE LIMIT: ND UPPER EXPLOSIVE LIMIT: ND

UNUSUAL FIRE & EXPLOSION HAZARDS: None known. SPECIAL FIRE FIGHTING PROCEDURES: None known.

SECTION V HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY: Eye contact, skin contact, inhalation, and ingestion.

EFFECTS OF OVEREXPOSURE: • Eves: Irritation. • Skin: Irritation. • Inhalation: Irritation of respiratory tract. • Ingestion: Harmful if swallowed.

EMERGENCY & FIRST AID PROCEDURES: • Eves: Flush eves with water for 15 minutes. • Skin: Flush with water for 15 minutes. Remove affected clothing.

• Inhalation: Remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration and get immediate medical attention.

Ingestion: DO NOT INDUCE VOMITING. Give large amounts of milk or water. Get immediate medical attention.

SECTION VI REACTIVITY DATA

STABILITY: Stable under normal conditions.

INCOMPATIBILITY (material to avoid): Strongly oxidizing agents.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

HAZARDOUS DECOMPOSITION PRODUCTS: None known.

SECTION VII SPILL OR LEAK PROCEDURES

IF RELEASED OR SPILLED: Contain spill, absorb with absorbent material, or recover to reuse if possible.

WASTE DISPOSAL METHOD: Dispose of according to federal, state and local laws. Can be disposed of with waste oil. Biodegradable.

SECTION VIII SPECIAL PROTECTION INFORMATION

MECHANICAL **VENTILATION:** LOCAL XXXXX OTHER

RESPIRATORY PROTECTION: If ventilation is inadequate, use an approved respirator.

EYE PROTECTION: Splash goggles.

PROTECTIVE GLOVES: Chemical resistant gloves.

OTHER PROTECTIVE EQUIPMENT: Follow industrial clothing standards.

SECTION IX SPECIAL PRECAUTIONS

HANDLING & STORING PRECAUTIONS: Store away from oxidizing agents. Keep away from extreme temperatures, whether hot or cold.

PREPARED: 11/19/92 UPDATED: 12/31/06 PRODUCT #: FLSC9500, FLSC95128-RTU, FLSC9505. FLSC9515P, FLSC9555