A COOR THEODY (A TION	MATERIAL SAFETY DATA SHEET			HAZARD RATING	
MFG'S INFORMATION			Health	2	
Finger Lakes Chemicals, Inc.	0-least, 1-slight, 2-moderate, 3-high,		Fire	1	
420 St. Paul Street	4-extreme, A - goggles, B - goggles &			-	
Rochester, NY 14605		- goggles & gloves &		Reactivity	0
1-800-876-0222	protective	wear		Personal	В
EMERGENCY (585) 275-3232		·			
	SEC	CTION I DESCRIPTION			
STOCK NUMBER		TRADE NAME AND			
		Finger Lakes Graffiti l	Remover		
CHEMICAL FAMILY		FORMULA			
	SECTION II	HAZARDOUS INGREDIE	NTS		
	CAS. NO.		(%)	TLV	
Alcohol Linear Surfactant	34398-01-1		<10		
2-Pyrrolidinone	872-50-4		>30		
Terpene Alcohol			<10		
Alpha Terpineol	98-55-5		>30		
DiBasic Ester (Mixture)	1119-49-0, 627-93-	-0, 106-55-0	>30		
		ION III PHYSICAL DATA			
BOILING POINT (0°F)	424°F	SPECIFIC GRAVITY	•	.995	
VAPOR PRESSURE	NA	PERCENT VOLATII		NA	
VAPOR DENSITY(Air =1)	>1	EVAPORATION RA			
SOLUBILITY IN WATER	Slight	APPEARANCE & O	DOR	Clear liquid/Faint p	ine odor
BOLODIEIT III WIII		E AND EXPLOSION HAZA	RD DATA		<del></del>
ELACUDODIT (mathed seed)		ABLE LIMITS	LEL	UEL	
FLASH POINT (method used) OVER 200°F TCC	FLAMMA	ABLE LIVIIIS	LLL	OLL	
EXTINGUISHING MEDIA: Dry	rahamiaal faam ar C	ron			
SPECIAL FIRE FIGHTING PRO	CEDIDES, Italia of C	out.	nut out fire Wa	ster is most effective u	hen
	CEDURES. USE DIA	anket of sinothering affect to p	ut out life. Wa	itel is illost effective w	iicii
used in a mist. UNUSUAL FIRE AND EXPLOS	TON HAZADDE. N	oma			
UNUSUAL FIRE AND EXPLOS			P. A.		
	SECTION	V HEALTH HAZARD DAT	<u>A</u>		
THRESHOLD LIMIT VALUE:					
EFFECTS OF OVER EXPOSUR	E: May cause irritat	ion to eyes or skin. May irrit	ation to mucus	membranes if inhaled	
EMERGENCY AND FIRST AID PROCEDURES: Flush eyes with water for 15 minutes. Remove contaminated clothing and wash skin with soap and water. If ingested, DO NOT induce vomiting. Drink large amounts of milk or water. Call a physician.					
wash skin with soap and water. I				ilk or water. Call a ph	ysician.
	SECTION	VI CONDITIONS TO AVO	<u>ID</u>		

STABILITY:

**UNSTABLE** 

STABLE XXXXXX

INCOMPATIBILITY (MAT'L TO AVOID): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: None

HAZARDOUS POLYMERIZATION:

MAY OCCUR

WON'T OCCUR XXXXX

CONDITIONS TO AVOID:

## SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Cleanup personnel must wear proper protective equipment. Reclaim material into a closed container for possible normal use or disposal.

WASTE DISPOSAL METHOD: Virgin material is not regulated by the Resource Conservation and Recovery Act. (40 CFR)

## SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: NIOSH approved organic respirator, if needed.

VENTILATION:

LOCAL XXXXXMECHANICAL

OTHER

PROTECTIVE GLOVES: Chemically resistant

EYE PROTECTION: Splash goggles

OTHER PROTECTIVE EQUIPMENT: Rubber apron and boots recommended.

## SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store away from heat and flames. May cause some affects to painted surfaces. Use solvent resistant equipment. Store in a cool place. KEEP OUT OF REACH OF CHILDREN.

PRODUCT #: FLSC-45

DATE PREPARED: 02/16/95

DATE REVISED: 01/18/02