

SECTION I - IDENTITY

#141 MORNING STAR
Hazardous - YES

Health	2
Flammability	0
Reactivity	0
Personal Protection	C

PERMA Incorporated
605 Springs Road
Bedford, MA. 01730

Telephone Number for Information
(978)667-5161

Date Prepared
11/01/99

Prepared By T. PITROLFFY

4 = Most Hazardous
Emergency Phone Number
1-800-255-3924 or Poison Center

SECTION II - HAZARDOUS INGREDIENTS

Hazardous Components CAS Reg#	PEL mg/m3	TWA mg/m3	STEL mg/m3	Other Limits %
BENZENE SULFONIC ACID CAS #27176-87-0	NA.	NA.	NA.	<10

*ASTERISKED CHEMICAL SUBJECT TO REPORTING REQUIREMENT OF SEC.313 TITLE III.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling point	- 212F	Specific Gravity(Water=1)	- 1.03
Vapor Pressure (mm Hg)	- 16	Melting Point	- N.A.
Vapor Density (air=1)	- 1.1	Evaporation Rate(Butyl Acetate=1)	- .38
Viscosity (CPS)	- 220	Decomposition Temperature	-N.A.
Auto Ignition Temp.	- NA.	Solubility in Water	-COMPLETE
pH - 1.5 +/- .5 Conc., 10%:2.5			
Appearance and Odor	-BLUE-GREEN LIQUID WITH FRAGRANCE		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point - N.A. Flammable Limits
LEL - N.A. UEL - N.A.

Extinguishing media - WATER

Fire Fighting Procedure - COOL CONTAINERS WITH WATER

Fire and Explosion Hazards - NON FLAMMABLE, BUT MAY REACT WITH MOST METALS
ON LONG CONTACT, WITH THE POSSIBLE EVOLUTION OF HYDROGEN

SECTION V - REACTIVITY DATA

Stability - STABLE
Conditions to Avoid - N.A.

Incompatibility - ALKALINE, MILD STEEL, ALUMINIUM
Hazardous Decomposition or Byproduct - NA.

Hazardous Polymerization - WILL NOT OCCUR
Conditions to Avoid - N.A.

The information herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or results to be obtained from use thereof.
Essentially similar to OSHA form # 174

SECTION VI - HEALTH HAZARD DATA

Routes of entry:
Inhalation - YES Skin - YES Ingestion - YES
Health Hazards-Acute: CAUSES CHEMICAL BURNS TO EYES, SKIN AND MUCOUS
MEMBRANES. CHRONIC: CHEMICAL BURNS AND/OR ULCERATION OF SKIN; MAY PERMA-
NENTLY DAMAGE EYES. TARGET ORGANS: EYES, RESP. SYS., UPPER GI. TRACT, SKIN
Carcinogenicity: NO
NTP - N.A. IARC Monographs - N.A. OSHA Regulated - NO
Signs and Symptoms of Exposure - REDNESS, IRRITATION OF EYES, SKIN OR
MUCOUS MEMBRANES

Medical Conditions Aggravated - SENSITIZED SKIN

Emergency and First Aid Procedures - IMMEDIATELY WASH CONTACT AREAS (EYES)
WITH LARGE QUANTITIES OF WATER FOR 15 MINUTES.
INGESTION: DRINK LARGE AMOUNTS OF WATER OR MILK, CALL PHYSICIAN.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled - DIKE AND
COLLECT MATERIAL INTO PLASTIC CONTAINER. WATER RINSE AND DRAIN, FLUSH
SMALL AMOUNTS. NEUTRALIZE WITH SODA, ASH OR LIME. (BIODEGRADABLE)
Waste Disposal Method - DISPOSE OF ACCORDING TO LOCAL, STATE AND FEDERAL
HAZARDOUS WASTE REGULATIONS; USE SANITARY LANDFILL.
EPA WASTE NO. D002

Precautions to be Taken in Handling and Storage -
USE ADEQUATE VENTILATION. DO NOT MIX WITH OTHER CHEMICALS.
AVOID PROLONGED CONTACT. KEEP FROM FREEZING AND EXCESSIVE HEAT

Other Precautions - STORE IN SECURE AREA. AVOID FOOD OR FEED CONTAMINATION.
RINSE EMPTY CONTAINERS BEFORE DISPOSAL. KEEP OUT OF REACH OF CHILDREN !

SECTION VIII - CONTROL MEASURES

Respiratory Protection - USE IN WELL VENTILATED AREA, FOLLOW DIRECTIONS,
AVOID INHALING MIST.

Ventilation Local Exhaust - RECOMMENDED
Mechanical - N.A.
Special - N.A.
Other - ASSURE FRESH AIR CIRCULATION.

Protective Gloves - REQUIRED: RUBBER, PLASTIC
Eye Protection - REQUIRED: SAFETY GLASSES, GOGGLES
Other Protection - RECOMMENDED: EYE WASH

Work/Hygienic Practices - DO NOT EAT, DRINK OR SMOKE NEXT TO MATERIAL.
WASH HANDS/FACE AFTER WORK.

SECTION IX - TRANSPORTATION

49 CFR

Unit Cont. - 55,30,5,1 GAL. PLASTIC CONT. Report Qty. (Lbs) - NA.
OSHA - IRRITANT Labels - NONE
DOT - NOT REGULATED
UN - NOT REGULATED

Vendor assumes no responsibility for injury to vendee or third person proximately caused if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Further more, vendee assumes the risk in use of the material.