

CLEANING LABORATORY EVALUATION SUMMARY

SCL #: 2021
 DateRun: 07/13/2021
 Experimenters: Ross Goding, Edward Judge
 ClientType: Lab
 ProjectNumber: Project #4
 Substrates: Glass/Quartz, Other, Chrome
 PartType: Coupon
 Contaminants: Glass
 Cleaning Methods: Manual Wipe
 Analytical Methods: Gravimetric, Visual

Purpose: To test the effectiveness of Clorox Liquid Bleach in the removal of Glass Soil from various substrates.

Experimental Procedure: A Clorox Liquid Bleach solution was created by mixing 4 (mL) parts liquid bleach and 192 (mL) parts water. Then, 3 coupons of each substrate (chrome, glass, mirror) were collected and initial weights were taken. SSL Soil 2 Glass Soil was applied to each coupon and allowed to air dry for 24 hours. After the 24 hour dry time, the weights of the newly contaminated coupons were measured. All coupons were placed into a Gardner-scrub Abrasion Tester machine. Wypall cleaning cloths were attached to each of the 3 cleaning blocks used for the test. Each Wypall cloth and all coupons received 2 sprays of the Clorox Liquid Bleach solution and the Gardner-scrub Abrasion Tester was run for 20 repetitions, simulating 20 manual wipes. Once cleaning concluded, the cleaned coupons were allowed to air dry for 24 hours. After 24 hours, the weights of the cleaned coupons were measured.

Cleaner	Substrate	Initial wt of cont.	Final wt of cont.	%Cont Removed	% AVG	% Overall
Clorox Liquid Bleach	Chrome	0.0782	0.0038	95.14	89.22	87.95
		0.0942	0.0040	95.75		
		0.0932	0.0274	70.60		
	Glass	0.0475	0.0022	95.37	89.42	
		0.0507	0.0030	94.08		
		0.0774	0.0164	78.81		
	Mirror	0.0269	0.0006	97.77	85.21	
		0.0354	0.0010	97.18		
		0.0379	0.0149	60.69		

Summary:		Substrates: Glass/Quartz, Other, Chrome			
		Contaminants: Glass			
Company Name:	Product Name:	Conc.:	Efficiency:	Effective:	Observations:
Clorox Company	Clorox Bleach	1/48	87.95	<input checked="" type="checkbox"/>	Clorox Liquid Bleach was effective in the removal of Glass Soil from various substrates.

Conclusion: Clorox Liquid Bleach was successful in removing Glass Soil from chrome, glass, and mirror substrates.