

# CLEANING LABORATORY EVALUATION SUMMARY

SCL #: 2012

DateRun: 08/14/2012

Experimenters: Junhee Cho, Johnny Le

ClientType: Cleaning Equipment Mfr

ProjectNumber: Project #1

Substrates: Vinyl Composite Tiles

PartType: Coupon

Contaminants: Greases, Food

Cleaning Methods: Manual Wipe

Analytical Methods: Gloss-Color Meter

Purpose: To evaluate supplied product for grease removal from floor surfaces following CSPA DCC 17

Experimental Procedure: Floor cleaning for the supplied product was tested using the CSPA DCC 17 - Greasy Soil Test Method for Evaluating Spray-and-Wipe Cleaners Used On Hard, Non-Glossy Surfaces standard. A few minor deviations from the standard were incorporated into the test conducted.

The Greasy Soil Test Method is a standard method that evaluates the cleaning performance of products intended for use on washable walls or other hard, non-glossy surfaces. This method provides instructions for soil application, cleaning and evaluation of spray-and-wipe cleaners under controlled cleaning conditions. This method can be used to assess product performance for cleaning a fabricated greasy soil blend applied to painted wallboard tiles. It is not inclusive of all soil or substrates typically encountered by a consumer while using these products.

Latex painted vinyl composite tiles were substituted for masonite wallboard tiles. These tiles were soiled with a mixture of melted, oily soils containing a small amount of carbon black. The tiles were dried overnight at room temperature. A measured amount of spray-and-wipe cleaner is applied to a reinforced paper towel was used in place of the sponge. The soaked towels were used to scrub a portion of the soiled substrate using a straight-line washability apparatus. The tile was rinsed after cleaning to remove loosened soil. Separate soiled coupons were cleaned with the other products being evaluated instead of using the same soiled coupon as another product.

This was done to eliminate any possible cross contamination of the cleaning process. Three coupons were cleaned by each cleaning product being evaluated. Cleaning performance was taken as a linear function of reflectance value, and visually evaluated by a panel of judges.

Coupon preparation:

Two coats of white paint solution were applied to the slightly rough side of the tiles, waiting 15 minutes between each coat. Coupons were allowed to dry overnight at room temperature, and then cure them at 50°C and 50% humidity for 24 hours. Five reflectance readings were taken for each of three separate tiles to obtain a baseline value.

Soil Preparation

A mixture of three cooking oils/greases was made. A melt blend of 33% vegetable shortening, 33% lard, 33% vegetable oil and 1% carbon lampblack was made up fresh for the testing. Care was taken in the application of the soil onto the coupons so that light and heavy areas were avoided. Allow the soiled tiles to dry for 24 hours at room temperature. Five reflectance readings were made for each of three soiled tiles to obtain a soiled reference value.

Cleaning Test

Place a soiled tile in the tray of the abrasion tester such that the direction of the soiling is perpendicular to the direction of the sponge. In place of using a sponge and pouring solution into dish for application, products were applied to the coated surfaces using 3-5 sprays from manual spray pump and 4-7 sprays onto the reinforced Wypal X60 paper towel attached to the cleaning instrument. The cleaning was performed using Gardner Straightline washability unit and conducted for the prescribed 5 cycles (10 strokes).

Following the initial cycle, there was no discernable difference between the products and an additional 15 cycles were run. The coupons were immediately rinse with tap water only the surface which was scrubbed.

Cleaning data can be calculated as percent detergency in the following equation:  

$$\% \text{ DET} = \frac{R(\text{cleaned}) - R(\text{soiled})}{R(\text{unsoiled}) - R(\text{soiled})} \times 100$$

ChemistriesEvaluated: Trio (Tartar 1g), Water, Clorox green work all-purpose cleaner, Clorox 409 all-purpose cleaner

Results: Based on the visual observations and the light meter reading comparisons (L values), the Trio cleaner performed less than the traditional all purpose (Clorox) cleaner. The Trio resulted in the light readings to return to 83% of the original reading. The Clorox product was over than 90%.

L* Readings					
-------------	--	--	--	--	--

## CLEANING LABORATORY EVALUATION SUMMARY

Product	Base	Dirty	Clean	%DET	Ave %
Trio (1g)					
	89.86	49.06	83.89	85.37	
	89.47	48.49	80.17	77.31	
	88.64	44.45	82.81	86.81	83.16
Water					
	90.86	44.17	83.30	83.81	
	89.78	54.25	82.26	78.83	
	90.68	32.24	81.16	83.71	82.12
Clorox Greenworks All Purpose					
	89.81	45.40	82.15	82.75	
	90.61	49.23	88.24	94.27	
	90.02	38.54	89.48	98.95	91.99
Clorox 409 all purpose cleaner					
	88.60	50.80	89.73	102.99	
	88.63	41.98	83.08	88.10	
	89.76	43.02	83.12	85.79	92.30

Summary:

<b>Substrates:</b>	Vinyl Composite Tiles				
<b>Contaminants:</b>	Greases, Food				
<b>Company Name:</b>	<b>Product Name:</b>	<b>Conc.:</b>	<b>Efficiency:</b>	<b>Effective:</b>	<b>Observations:</b>
GenEon	GenEon Solution	100	83.16	<input type="checkbox"/>	
Water	Water	100	82.12	<input type="checkbox"/>	
Clorox Company	Green Works Multi-Surface Cleaner	100	91.99	<input checked="" type="checkbox"/>	
Clorox Company	Formula 409 All Purpose Cleaner	100	92.30	<input checked="" type="checkbox"/>	

Conclusion:

The supplied product was found to be less effective than the traditional product in removing the food grease mixture from painted tiles using manual wiping.